

## DESCRIPTION


KESDR0524PMUTAG is ultra-low capacitance Transient Voltage Suppressor (TVS) designed to protection for high-speed data interfaces. With typical capacitance of 0.2pF (I/O to I/O) only, KESDR0524PMUTAG designed to protect parasitic-sensitive systems against over-voltage and over-current transient events. It complies with IEC 61000-4-2 (ESD), Level 4(±15KV air, ±8KV contact discharge), IEC61000-4-4 (electrical fast transient-EFT) (40A, 5/50ns),very fast charged device model (CDM) ESD and cable discharge event(CDE), etc.

KESDR0524PMUTAG device can protect four high-speed data lines. The combined features of ultra-low capacitance, ultra-small size and high ESD robustness make KESDR0524PMUTAG for high-speed data ports and high-frequency lines (e.g., HDMI & DVI) applications. The low clamping voltage of KESDR0524PMUTAG guarantees a minimum stress on the protected IC.

## ORDERING INFORMATION

- ✧ Device: KESDR0524PMUTAG
- ✧ Package: DFN2510
- ✧ Material: Halogen free
- ✧ Packing: Tape & Reel
- ✧ Quantity per reel: 3,000pcs

## PIN CONFIGURATION



## FEATURES

- ✧ Transient protection for high-speed data lines  
IEC 61000-4-2(ESD) ±25KV(Air)  
±20KV(Contact)  
IEC 61000-4-4(EFT)40A(5/50ns)  
Cable Discharge Event(CDE)
- ✧ Package optimized for high-speed lines
- ✧ Ultra-small package(2.5mm\*1.0mm\*0.5mm)
- ✧ Protects four data lines
- ✧ Low capacitance: 0.2pF (I/O to I/O)
- ✧ Low leakage current
- ✧ Low clamping voltage
- ✧ Each I/O pin can withstand over 1000 ESD strikes for ±8KV contact discharge

## MACHANICAL DATA

- ✧ DFN2510 package
- ✧ Flammability Rating: UL 94V-0
- ✧ Terminal: Matte tin plated.
- ✧ Packaging: Tape and Reel
- ✧ High temperature soldering guaranteed:260℃/10s
- ✧ Reel size: 7 inch

## APPLICATIONS

- ✧ Serial ATA
- ✧ PCI Express
- ✧ Desktops, Servers and Notebooks
- ✧ MDDI Ports
- ✧ USB 2.0/3.0 Power and Data Line Protection
- ✧ Display Ports
- ✧ High Definition Multi-Media Interface (HDMI)
- ✧ Digital Visual Interface (DVI)

## PACKAGE OUTLINE



### ABSOLUTE MAXIMUM RATING

| Symbol           | Parameter                                                      | Value      | Units |
|------------------|----------------------------------------------------------------|------------|-------|
| P <sub>PP</sub>  | Peak Pulse Power (8/20μs)                                      | 60         | W     |
| V <sub>ESD</sub> | ESD per IEC 61000-4-2 (Air)<br>ESD per IEC 61000-4-2 (Contact) | ±25<br>±20 | kV    |
| T <sub>OPT</sub> | Operating Temperature                                          | -55/+125   | °C    |
| T <sub>STG</sub> | Storage Temperature                                            | -55/+150   | °C    |


### ELECTRICAL CHARACTERISTICS (T<sub>amb</sub>=25°C)

| Symbol           | Parameter                 | Test Condition                                                      | Min | Typ | Max | Units |
|------------------|---------------------------|---------------------------------------------------------------------|-----|-----|-----|-------|
| V <sub>RWM</sub> | Reverse Working Voltage   | Any I/O pin to GND                                                  |     |     | 5.0 | V     |
| V <sub>BR</sub>  | Reverse Breakdown Voltage | I <sub>T</sub> = 1mA<br>Any I/O pin to GND                          | 6.0 |     | 9.0 | V     |
| I <sub>R</sub>   | Reverse Leakage Current   | V <sub>RWM</sub> = 5V<br>Any I/O pin to GND                         |     |     | 1.0 | μA    |
| V <sub>C</sub>   | Clamping Voltage          | I <sub>PP</sub> = 1A, t <sub>p</sub> = 8/20μs<br>Any I/O pin to GND |     |     | 10  | V     |
| V <sub>C</sub>   | Clamping Voltage          | I <sub>PP</sub> = 4A, t <sub>p</sub> = 8/20μs<br>Any I/O pin to GND |     |     | 15  | V     |
| C <sub>ESD</sub> | Parasitic Capacitance     | V <sub>R</sub> = 0V, f = 1MHz<br>Between I/O and GND                |     | 0.4 | 0.5 | pF    |
| C <sub>ESD</sub> | Parasitic Capacitance     | V <sub>R</sub> = 0V, f = 1MHz<br>Between I/O and I/O                |     | 0.2 | 0.3 | pF    |


Note: I/O pins are pin 1,2,4,5, GND pins are pin 3,8.

**ELECTRICAL CHARACTERISTICS CURVE**


**Fig 1 Power Derating Curve**




**Fig 2 Clamping Voltage vs Peak Pulse Current**




**Fig 3 Voltage Sweeping of I/O to I/O**




**Fig 4 Voltage vs Capacitance**




**Fig 5 ESD Clamping of I/O to GND  
(+8kV Contact per IEC 61000-4-2)**



**Fig 6 ESD Clamping of I/O to GND  
(-8kV Contact per IEC 61000-4-2)**



**DFN2510 PACKAGE OUTLINE DIMENSIONS**


| Symbol | Dimensions (mm) |       |      |
|--------|-----------------|-------|------|
|        | Min.            | Nom.  | Max. |
| D      | 2.45            | 2.50  | 2.55 |
| E      | 0.95            | 1.00  | 1.05 |
| b1     | 0.35            | 0.40  | 0.45 |
| b2     | 0.20REF         |       |      |
| b      | 0.15            | 0.20  | 0.25 |
| L      | 0.33            | 0.38  | 0.43 |
| Nd     | 2.00BSC         |       |      |
| e      | 0.50BSC         |       |      |
| R      | 0.10            | 0.125 | 0.15 |
| A      | 0.45            | 0.50  | 0.55 |
| c      | 0.15REF         |       |      |
| A1     | 0.00            | -     | 0.05 |